

**High Performance LNB
Low Budget price**



**2 Jahre Garantie!
2 years warranty!**

**Technische Daten /
technical data**

Modell	BW 40 WB
Art.Nr.	L74
EAN	-
Anwendung / Application	Universal Wideband für Multischalterbetrieb / Universal Wideband for Multiswitch usage
Eingangsfrequenz / Input frequency	10,70 - 12,75 GHz
Ausgangsfrequenz / Output frequency	300 - 2350 MHz
Lokale Oszillator Frequenz / Local Oscillator Frequency (LOF)	10,40 GHz
L.O.F Stabilität / L.O.F Stability	+/- 1 MHz (25°C) / +/- 5 MHz (-40°C - 60°C)
Rauschmass / Noise figure	0,5 dB typ.
Verstärkung / Gain	55 - 65 dB
Kreuzpolarisations-Entkopplung / Cross polar isolation	> 20 dB
Anschlüsse / Connections	2 (1 x Horizontal ; 1 x Vertikale Polarität) / 2 (1 x horizontal ; 1 x vertical polarity)
Anschluss-Typ / Connection type	75 Ohm F-Buchse/ 75 Ohm F-type female
Feeddurchmesser / Feed diameter	40 mm
Spannungsversorgung / Operating voltage	10,0 - 19,0 V
Stromaufnahme / Current consumption	ca. 105 mA typ.
Umgebungstemperatur / Operating Temperature	-40°C - +60°C

**Universal Wideband LNB
40 mm Feedhorn**

**innovative solutions
bauckhage - wiehl**